

# CLOG

MAXIMUM  
PERFORMANCE



For professionals who work in the most demanding environments, the **CLOG** is the ideal style.

## Description

**CLOG**, is a bicolored occupational clog entirely made of polymeric materials and with the following components:

- Antistatic insert;
- Heel-strap;
- Removable insole;
- Ventilation holes — both on clog and insole.

## Users

**CLOG**, is ideal for activities in which professionals spend many hours standing and, who hence have a tendency to suffer foot discomfort or lower body fatigue, especially to be used in:



Operation  
Room



Hospitals and Other  
Healthcare Institutions



Pharmaceutical  
Industry

## Specifications



### Sterilizable

Produced in an high quality polymer which allows sterilization in autoclave up to 134 °C.



### Removable Insole

It's detachable to allow a deeper cleaning.



### Shock Absorption

The special design helps to reduce the occurrence of micro-lesions in tendons, bones and joints, and the feeling of tired legs.



### Antistatic

Promotes the dissipation of accumulated static electricity.



### Upper Liquid Protection

Avoids the entrance of liquids inside the shoe.



### Breathable

Regulates the temperature and humidity of the foot.



### Removable Strap

Increases comfort and support to the heel, as well as keeps your foot firmly in the footwear.



### Washable

The footwear can be machine washed up to 90 °C.



### Antislip

The sole is designed to reduce the risk of slipping.



### ESD \*

Dissipates electrostatic build-up during use preventing accidental discharges. According to standard IEC 61340-5.1 and IEC 61340-4.3.



### Lemon Scent

The footwear has a fresh and soft fragrance, with a lemon scent.



### Unisex

Style designed to be worn by men and women.

## Materials and Technologies



**CLOG** is made with **Steri-tech™** technology. Its material allows sterilization up to 134 °C, is non-toxic and provides odor resistance, bacterial and fungal growth inhibition.



**CLOG**'s exclusive Steri-tech™ insole uses **Grid Design™** technology to improve its shock absorption capacity, while being highly flexible and breathable to allow maximum comfort.

\* Only applies to CLOG ESD.



## Technical Standard



**CE** In accordance with directive 89/686/EEC.



**EN ISO 20347: 2012** Personal protective equipment — Occupational footwear, class II.



**Norma IEC 61340-5.1.** — Electrical resistance. \*  
**Norma IEC 61340-4.3.** — Electrical resistance. — Class 1 \*



**SATRA TM 144: 2011** Friction (slip resistance) of footwear and floorings test.  
**SATRA TM 158: 1992** Washability

## Technical Specifications

- Heat resistance — autoclavable up to a maximum of 134 °C;
- Slip-resistant;
- Resistant to abrasion;
- Resistant to detergents;
- Resistant to lactic acid;
- Resistant to liquids (such as infiltration of blood);
- Resistant to chemicals;
- Resistant to saltwater;
- Recyclable.

## Care and Cleaning

**Wash:** Machine washable up to a maximum temperature of 90 °C. Can also be steam sterilized in autoclave up to 134 °C.

**Dry:** Wipe with a cloth or dry at room temperature.

## Attention

**CLOG** resists to several sterilizations in autoclave, but durability might be impaired depending on sterilization parameters and number of cycles. **CLOG** also resists to several washings at 90 °C in washing machine. It is not recommended the use of bleaching agents during washing machine cycles at 90 °C. The resistance of **CLOG** material to washing depends on several factors:

- Type of detergent;
- Concentration;
- Cycles' duration;
- Temperature;
- Physical stress during the cycles.

**WOCK®**  
Professional Footwear