JUJH

NUBE was designed to assure an excellent antislip performance, allowing you to reach further and more comfortably.

Description

NUBE, this occupational clog is entirely made of polymeric materials and has the following components:

- Spillage protection device:
- Evergrip™ rubber track;
- Antistatic insert.

Users

NUBE, is ideal for uses where prolonged standing or walking may tend to induce foot discomfort or lower body fatigue, especially to be used in:



Swimming Pool Areas



Hospitals and Other Healthcare Institutions

Specifications

Super Light

Feelite™ technology produces remarkably light, resistant and comfortable footwear.

Antislip

The sole is designed to reduce the risk of slipping - SRC Antislip approved.

Optional Insole

Allows you to raise even more your comfort.

Coolmax[®] Technology

The Coolmax® insole allows air to circulate inside the shoe, drying humidity faster and keeping the feet drier.

Shock Absorption

The special design helps to reduce the occurrence of micro-lesions in tendons, bones and joints, and the feeling of tired legs.

Antistatic

Promotes the dissipation of accumulated static electricity.

Upper Liquid Protection

Avoids the entrance of liquids inside the shoe.

Spillage Protection

Allows to choose between extra ventilation or superior protection, which prevents the entrance of liquids into the footwear.

Breathable

Regulates the temperature and humidity of the foot.

Washable

The footwear can be machine washed up to 50 °C.*

τüν

тΰ\

This footwear was tested and approved by TÜV Institute in Germany, for its antislip and antistatic properties.


Unisex 윙입


Style designed to be worn by men and women.

Materials and Technologies



NUBE is made with Feelite™ technology. Its material is super lightweight and provides odor resistance, inhibits proliferation of bacteria and is non-toxic.







Technical Standard

CE



In accordance with directive 89/686/EEC.

EN ISO EN ISO 20347: 2012 Personal protective equipment — Occupational footwear, class II. EN ISO 20347: 2012 (5.3.4.4) Slip resistance on ceramic tile floor with SLS and on steel floor with glycerine - SRC.

SATR/

SATRA TM 158: 1992 Washability

Technical Specifications

- SRC Slip-resistant;
- Heat resistance machine washable up to a maximum of $50 \degree$ C;
- Resistant to abrasion:
- Everlite™ Fuel oil resistant: .
- Resistant to detergents; Resistant to lactic acid; .
- Resistant to liquids (such as infiltration of blood);
- Resistant to chemicals:
- Resistant to saltwater.
- Resistant to animal fat.

Care and Cleaning

Wash: Machine washable up to a maximum temperature of 50 °C. Can also be cold sterilized with chlorine, sodium hypochlorite or hydrogen peroxide. Dry: Wipe with a cloth or dry at room temperature.

Attention

NUBE resists several washings at 50 °C in washing machine. It is not recommended the use of bleaching agents during washing machine cycles at 50 °C. The resistance of NUBE material to washing depends on several factors:

- Type of detergent;
- Concentration;
- Cycles' duration;
- Temperature;
- Physical stress during the cycles.

* Optional insole is not machine washable.

